



1020

MOLD GUARD

PRODUCT APPLICATIONS

ShieldAll 1020 is a white low gloss surface primer and coating that can be applied over various building construction materials including wood, wood composites, gypsum wall board, ceiling tile, concrete and brick, as well as painted surfaces. It has excellent water resistance, and resistance to bleed-through of stains.

ShieldAll 1020 is hydrophobic, and will inhibit water penetration through the sealed surface, as well as minimize the accumulation of debris on its surface. It breathes well allowing moisture vapor to permeate the film at recommended coverage rates. It provides an easy to clean surface.

ShieldAll 1020 has long term microbial resistance properties which protect it from fungal or mold growth on its surface. It will inhibit microbial growth on its surface even in damp environments.

ShieldAll 1020 is low in odor and non-hazardous to apply and use. The VOC is less than 0.01 lbs/gallon.

Protective Chemistries Inc.
P.O. Box 17396
Minneapolis, MN 55417
protectchem.com

WARNING This product does not protect the user or others against bacteria, viruses, germs, or other disease organisms. For trained professional use only. Do not add water or any thinning agent. Protect from freezing and direct sunlight. Store between 40°F (4°C) AND 100°F (38°C)

CAUTION

INGESTION: May cause the following effects: abdominal discomfort, nausea, vomiting or diarrhea. **SKIN:** May cause minor skin irritation and dermatitis. **RESPIRATORY TRACT:** May cause minor respiratory irritation. **EYE:** May cause mild discomfort, tearing and reddening.

FIRST AID

INGESTION: Administer 3-4 glasses of milk or water. Do not induce vomiting. Seek medical advice. **SKIN:** Remove contaminated clothing. Wash skin with soap and water. Obtain medical attention if irritation persists. **INHALATION:** Remove to fresh air. Obtain medical attention if symptom persists. **EYE:** Immediately flush eyes with water and continue washing for several minutes. Obtain medical attention if discomfort persists.

IN CASE OF FIRE

Use water spray, foam, dry chemical or carbon dioxide. Use self-contained breathing apparatus when fighting fires in enclosed areas.

IN CASE OF SPILLS

Keep spilled product out of sewers, watersheds, or water systems. Cover with absorbent or contain. Collect for disposal. Observe government regulations.

HANDLING AND STORAGE

KEEP OUT OF REACH OF CHILDREN. Wear safety glasses and gloves to avoid contact with eyes, skin and clothing. Keep container closed when not in use. Use only with adequate ventilation.

TO REORDER GO TO: myShieldAll.com

WHITE MOLD RESISTANT COATING

5 U.S. GALLONS (18.9 LITERS)

HMIS RATINGS
FLAMMABILITY 0
REACTIVITY 0
HEALTH 1



Made in America

DIRECTIONS

MATERIAL PREPARATION Apply only to clean, dry surfaces. Keep container closed when not in use. Do Not Thin. Stir before use if any separation has occurred.

SURFACE PREPARATION All surfaces should be thoroughly cleaned to remove all mold, dust and loose particles. Pre-clean and disinfect mold or mildew contaminated surfaces. Glossy surfaces may require light sanding to obtain good adhesion.

APPLICATION Apply uniformly to building exterior surfaces or onto interior wall, ceiling, or panel surfaces at a rate of 500-700 ft²/gallon until a thin uniform film remains on the surface. Porous surfaces may require lower coverage rates or two coats to completely seal the surface. Use two coats to obtain improved exterior durability, or to obtain improved whiteness and surface hiding. It can be sprayed with any airless equipment using a 0.13 - 0.15 mil spray tip, or applied with a brush or paint roller.

CLEAN-UP Clean up spills immediately before they have a chance to dry. Use fresh water to clean application equipment before product dries. Flush spray equipment with a cleaning solution of 1/2 cup pine oil cleaner, 1/2 cup sudsy ammonia and 4 gallons of water. Flush until material exiting the pump shows no evidence of product. Dry product may be removed with solvents such as chlorinated solvents, or undiluted pine oil or citrus based cleaners.

LIMITATIONS Store and apply between 40°F and 100°F. Protect from freezing. Product shelf life is approximately 1 year when stored between 40°F and 100°F.

WARRANTY: Seller will not accept liability for more than product replacement or refund. Any claim regarding product defect must be received in writing within 6 months from the date of shipment. Seller makes no other Warranty or Guarantee, express or implied, including warranties of fitness for a particular purpose or merchantability. The Seller shall assume no other liability for incidental or consequential damages arising out of the sale or use of this product.

DISCLAIMER We believe that the information provided in this label is correct to the best of our knowledge and tests. The usage directions and recommendations are herein made without guarantee or representation as to results. We recommend that suitability and usage of this product be performed by the user to determine if this product meets all his/her requirements. In no event will the seller be liable for any consequential damages arising out of the use of this product.